

PROFESSIONAL SOLUTIONS

FOR SECURITY & COMFORT



Hubs



Also available in black

CP423W 20294**Ajax Hub 2 Plus White**

- Up to 200 devices
- Up to 100 cameras
- Up to 200 App users
- Up to 25 alarm groups
- Maximum 64 scenarios
- Visual alarm verification
- Battery backup - up to 16 hours
- Operating frequencies - 868.0 - 868.6 MHz
- Communication channels: Ethernet, Wi-Fi & LTE Sim
- **Black, CP423B - 20276**



Also available in black

CP424W 33152**Ajax Hub 2 4G White**

- Up to 100 detectors
- Up to 25 cameras
- Up to 50 app users
- Up to 9 alarm groups
- Up to 32 scenarios
- Visual alarm verification
- Power supply: 110 - 240VAC
- Battery backup - up to 16 hours
- Operating frequencies - 868.0 - 868.6 MHz
- Communication channels: Ethernet & 4G
- **Black, CP424B - 33151**

PSUs

**PS425** 27418.94.NC**Ajax PSU for Hub 2 Plus & ReX 2**

- Compatibility: Hub 2/Hub 2 Plus and Rex 2
- Input voltage: 8-32V DC
- Output voltage: 4.8 V DC 5%
- Switch on voltage: 8 V DC 2.5%
- Switch off voltage: 7-7.5V DC (depending on load)
- Max output current: 1.5 A

PSUs

**CP450W** 20294**Ajax StarterKit Cam Plus**

- 1 x Hub 2 Plus
- 1 x MotionCam
- 1 x Door Protect
- 1 x Space Control

Power Supply Units

CP424W**BATTERY****REGAL****Your one stop security shop**

From our warehouse to your front door



Delivery available across SA



Quotes are customised for your business



Secure payment gateway

www.regalsecurity.co.za | National Support Centre: 087 802 3920

CCTV & NVR'S


CC720 64923.197.WH1

Ajax - TurretCam

- Compatibility: Hub/HubPlus/Hub2(2G)/Hub2(4G)/Hub2Plus/Hub Hybrid
- 5MP/2.8mm
- JetSparrow Video Protocol
- Storage on NVR or SD card
- Codec: H.264 and H.265
- WDR and HDR dynamic Range
- TCP/IP - up to 100 Mbps
- AI Object Detection
- Smart IR up to 35m
- Visual verification of Ajax Alarms
- Microphone


CC721 79028.217.WH1

Ajax - BulletCam

- Compatibility: Hub/HubPlus/Hub2(2G)/Hub2(4G)/Hub2Plus/Hub Hybrid
- 5MP/2.8mm
- JetSparrow Video Protocol
- Storage on NVR or SD card
- Codec: H.264 and H.265
- WDR and HDR dynamic Range
- TCP/IP - up to 100 Mbps
- AI Object Detection
- Smart IR up to 35m
- Visual verification of Ajax Alarms
- Microphone


CC722 76018.214.WH1

Ajax - DomeCam Mini

- Compatibility: Hub/HubPlus/Hub2(2G)/Hub2(4G)/Hub2Plus/Hub Hybrid
- 5MP/2.8mm
- JetSparrow Video Protocol
- Storage on NVR or SD card
- Codec: H.264 and H.265
- WDR and HDR dynamic Range
- TCP/IP - up to 100 Mbps
- AI Object Detection
- Smart IR up to 30m
- Visual verification of Ajax Alarms
- Microphone


CD401W 70936.122.WH

Ajax 8 Channel NVR White

- 8 Channels
- Peer-to-peer streaming
- Instant live view
- Fast archive navigation with filters and calendar
- Dual streaming for instant preview
- Video clip export in a few clicks
- Real-Time oversight with a customizable video wall
- Video Stream with TLS encryption

CCTV & NVR'S

Motion & Glass Break Detectors


CD402W 70934.122.WH

Ajax 16 Channel NVR White

- 16 Channels
- Peer-to-peer streaming
- Instant live view
- Fast archive navigation with filters and calendar
- Dual streaming for instant preview
- Video clip export in a few clicks
- Real-Time oversight with a customizable video wall
- Video Stream with TLS encryption



Also available in black

BD420W 5328

Ajax MotionProtect White

- Sensing element: PIR sensor
- Motion detection distance: up to 12m
- Detection angles: Horizontal - 88.5°, Vertical - 80°
- Recommended installation height: 2.4 m
- Pet immunity: Weight - up to 20 kg, Height - up to 50 cm
- Up to 1700m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6MHz
- Battery: CR123A battery, 3V
- Battery life: up to 5 years
- Dimensions: 110 × 65 × 50 mm
- **Black, BD420B - 5314**


BD422W 8227

Ajax MotionProtect Plus White

- Sensing element: PIR sensor, microwave sensor (2.4GHz)
- Motion detection distance: up to 12m
- Detection angles: Horizontal - 88.5°, Vertical - 80°
- Recommended installation height: 2.4 m
- Pet immunity: Weight - up to 20 kg, Height - up to 50 cm
- Up to 1700m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6MHz
- Battery: CR123A battery, 3V
- Battery life: up to 5 years
- Dimensions: 110 × 65 × 50 mm


BD423W 7170

Ajax CombiProtect White

- Combined motion and glass break detector
- Motion detection distance: up to 12m
- Break detection distance: up to 9m
- Break detection angle: 180°
- Detection angles: Horizontal - 88.5°, Vertical - 80°
- Recommended installation height: 2.4 m
- Pet immunity: Weight - up to 20 kg, Height - up to 50 cm
- Up to 1700m in an open space (in a perfect environment)
- Operating frequencies: 868.0 - 868.6 MHz
- Battery: CR123A battery, 3 V
- Battery life: up to 5 years
- Dimensions: 110 × 65 × 50 mm

Door Contacts



Also available in black

MC420W 7063

Ajax DoorProtect White

- Installation: Indoors
- Activation threshold: Small Magnet - 1cm
- Up to 1200m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Power supply: CR123A battery (pre-installed)
- Battery life: up to 5 years
- Dimensions: Diameter - 20 mm, Height - 90 mm
- Dimensions: 150 × 103 × 14 mm
- **Black, MC420B - 7062**



Also available in black

MC422W 9999

Ajax DoorProtect Plus White

- Combined door contact and vibration detector
- Installation: Indoors
- Activation threshold: Small Magnet - 1 cm
- Up to 1200m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Power supply: CR123A battery (pre-installed)
- Battery life: up to 5 years
- Dimensions: Diameter - 20 mm, Height - 90 mm
- **Black, MC422W - 9996**


BD423W

Motion & Glass Break Detectors

**BD425W** 13268**Ajax MotionProtect Curtain White**

- Sensing element: Two PIR sensors
- Motion detection distance: from 6 to 15 meters (depending on the device settings)
- Detection angles: Horizontally - 6°, Vertically - 90°
- Recommended installation height: 2.4 m
- Up to 1700m in an open space (in a perfect environment)
- Operating frequencies: 868.0 - 868.6 MHz
- Battery life: up to 3 years
- Protection class: IP54
- Battery: CR123A, 3 V
- Dimensions: 134 × 44 × 34 mm

**BD426W** 26072**Ajax DualCurtain Outdoor White - Anti-Masking Motion Detector 30m**

- Compatibility: Hub Plus, Hub 2, Hub 2 Plus, ReX
- Sensing element: IR sensor, 2 on each side
- Motion detection distance: 4 to 15 meters (on each side, depends on settings)
- Up to 1,700 m in an open space (in a perfect environment)
- Power supply: 2 CR123 batteries, 3 V
- Battery life: Up to 4 years
- Protection class: IP54
- Operating temperature range: -25°C to +60°C
- Operating humidity: Up to 95%
- Dimensions: 174 × 123 × 88 mm

**BD427W** 12895**Ajax MotionProtect Outdoor White**

- Sensing element: Two PIR sensors
- Installation: Outdoors/indoors
- Recommended installation height: 0.8 - 1.3 m
- Detection angle: Horizontal - 90°
- Motion detection distance: Adjustable, 3 - 15 m
- Pet immunity: Height - up to 80 cm
- Up to 1700m in an open space (in a perfect environment)
- Battery life: up to 5 years
- Protection class: IP55
- Dimensions: 183 × 70 × 65 mm

**BD427-1W** 20309**Ajax Hood For MotionProtect Outdoor White**

- Mounting method: Dual lock tape
- Material: Polycarbonate



Also available in black

BD428W 5288**Ajax GlassProtect White**

- Sensing element: Electret microphone
- Break detection distance: Up to 9 m
- Microphone coverage angle: 180°
- Up to 1000m in an open space (in a perfect environment)
- Operating frequencies: 868.0 - 868.6 MHz
- Battery: CR123A battery, 3 V
- Battery life: up to 7 years
- Dimensions: Diameter - 20mm, Height - 90mm
- **Black, BD428B - 5236**

VALUE ADDED SERVICES

«REGAL»



PIR & Cameras



Also available in black

CC550W 10309**Ajax MotionCam Indoor White**

- Compatibility: Only with Hub 2, Hub 2 Plus
- Motion detection distance: up to 12 m
- Pet immunity: Weight - up to 20 kg, Height - up to 50 cm
- Detection angles: Horizontal - 88.5°, Vertical - 80°
- Camera view angle: 90°
- Photo quality: up to 640 × 480
- Recommended installation height: 2.4 m
- Up to 1700m in an open space
- Batteries: 2 x CR123A, 3 V
- Battery life: up to 4 years (up to 2.5 years if "Delay when entering" setting is activated)
- **Black, CC550B - 10308**



Also available in black

CC551W 36489**Ajax MotionCam (PhOD) White**

- Compatibility: Only with Hub 2, Hub 2 Plus
- Motion detection distance: up to 12 m
- Pet immunity: Weight - up to 20 kg, Height - up to 50 cm
- Detection angles: Horizontal - 88.5°, Vertical - 80°
- Camera view angle: 90°
- Photo quality: up to 640 × 480
- Recommended installation height: 2.4 m
- Up to 1700m in an open space
- Batteries: 2 x CR123A, 3 V
- Battery life: up to 4 years (up to 2.5 years if "Delay when entering" setting is activated)
- **Black, CC551B - 36488**

**CC552W** 26074**Ajax MotionCam Outdoor**

- Compatibility: Hub 2, Hub 2 Plus
- Recommended installation height: 0.8 - 1.3 m
- Sensing element: 2 x PIR sensor
- Motion detection distance: Adjustable, from 3 to 15 m
- Pet immunity: Up to 80 cm tall
- Detection angle: Horizontal 88.5° Vertical 80°
- Camera's angle: Horizontal 105° Vertical 102°
- Photo resolution: 320 × 176 pixels (by default) ; 640 × 352 pixels
- Shooting series up to 5 photos
- Infrared light for shooting in the dark: Available
- Power supply: 4 x CR123A batteries
- Up to 1,700m in an open space
- Battery life: Up to 3 years

**CC553W** 36660**Ajax MotionCam Outdoor (PhOD)**

- Compatibility: Hub 2, Hub 2 Plus
- Recommended installation height: 0.8 - 1.3 m
- Sensing element: 2 x PIR sensor
- Motion detection distance: Adjustable, from 3 to 15 m
- Pet immunity: Up to 80 cm tall
- Detection angle: Horizontal 88.5° Vertical 80°
- Camera's angle: Horizontal 105° Vertical 102°
- Photo resolution: 320 × 176 pixels (by default) ; 640 × 352 pixels
- Shooting series up to 5 photos
- Infrared light for shooting in the dark: Available
- Power supply: 4 x CR123A batteries
- Up to 1,700m in an open space
- Battery life: Up to 3 years

Keypads & Remotes



Also available in black

CP430W 8706**Ajax Keypad White**

- Numeric touch keypad
- Clear button
- Function button
- Arming button
- Disarming button
- Night mode button
- Tamper button
- Up to 1700m in an open space (in a perfect environment)
- Battery: 4 × AAA batteries, 3 V
- Battery life: up to 2 years
- Dimensions: 150 × 103 × 14 mm
- **Black, CP430B - 8722**

**CP431W** 26078**Ajax Keypad Plus White**

- Installation: Indoor only
- Compatibility: Hub Plus, Hub 2, Hub 2 Plus, ReX
- Personal passcodes: Yes
- Passcode guessing protection: Yes
- Duress code: Yes
- Contactless access: DESFire® EV1, EV2 ISO14443-A (13.56MHz)
- Power supply: Batteries: 4 lithium AA (FR6) Voltage 1.5V
- Battery life: up to 4.5 years
- Dimensions: 165 × 113 × 20 mm

**CP432W** 58455.148.WH1**Ajax Keypad Touchscreen White**

- Touch IPS display with a diagonal of 5 inches
- Operation with Secured cards and key fobs
- Control via smartphone due to BLE support
- Easy security group management
- Automation control
- Sound notifications about delays door openings and alarms
- **Black, CP432B - 58454.148.BL1**

**SW422W** 23528**Ajax Tag White**

- Compatibility: KeyPad Plus
- Communication technology: DESFire®
- Operating standard: ISO 14443-A (13.56 MHz)
- Encryption: Yes
- Authentication: Yes
- Protection from signal interception: Yes
- Possibility to assign the user: Yes
- Maximum number of bound hubs: Up to 13
- Overall dimensions: 45 × 32 × 6 mm



Keypad Plus

Wireless touch keypad supporting encrypted contactless cards and key fobs

CP431W**CP431B**

Also available in black

SW424W 6267**Ajax SpaceControl White**

- Four-button key fob with command delivery indication
- Battery: CR2032 battery, 3 V
- Battery life: up to 5 years
- Up to 1300m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Dimensions: 65 × 37 × 10 mm
- **Black, SW424B - 6108**



Also available in black

SW420W 10315**Ajax Button White**

- Command delivery confirmation
- Encryption with a modified AES algorithm
- Code hopping frequency
- Two modes: panic/control button
- Protected from accidental activation
- Operates with all Ajax Hubs and range extenders
- Up to 1300m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Battery life of up to 5 years
- Protection class: IP55
- Pre-installed CR2032 battery
- Dimensions: 47 × 35 × 13 mm
- **Black, SW420B - 10314**



Also available in black

SW421W 21658**Ajax Holder for Button**

- Excludes button SW420W
- **Black, SW421B - 21657**

**SW429W**

PREVENT SERIOUS WATER DAMAGE

Modules & Accessories



Also available in black

CP440W 8001**Ajax Rex White**

- Environment: Indoors
- Supports all Ajax Hubs
- Doesn't support MotionCam
- Max Number of Connected ReX per Hub - Hub - 1, - Hub Plus/Hub 2/Hub 2 Plus - 5
- Power supply - 110 - 240 VAC
- Built-in back-up battery: Li-Ion 2 Ah
- Battery backup - up to 35 hours
- Up to 1800m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Self-adjusting RF output power - up to 25 mW
- Dimensions: 163 × 163 × 36 mm
- **Black, CP440B - 8075**

**CP441B** 20354**Ajax MultiTransmitter**

- 18 Wired zones for connecting third-party detectors
- NO, NC (without R), EOL (NC with R), EOL (NO with R)
- Remote setup of connected detectors in the app
- Power supply for connected detectors: 12 VDC, 1A
- Up to 2000m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Power supply: 110 - 255 VAC
- Battery backup: 4 or 7 Ah capacity (not included)
- Dimensions: 196 × 238 × 100 mm

**CP442W** 32669**Ajax ReX 2 White**

- Environment: Indoors
- Compatibility Hub 2 and Hub 2 Plus
- Supports MotionCam
- Max Number of Connected ReX per Hub: 5
- Power supply - 110 - 240 VAC
- 12V option when using PSU module
- Built-in back-up battery: Li-Ion 2 Ah
- Battery backup - up to 35 hours
- Up to 1700m in an open space (in a perfect environment)
- Two-way communication between devices
- Operating frequencies - 868.0 - 868.6 MHz
- Self-adjusting RF output power - up to 25 mW
- Dimensions: 163 × 163 × 36 mm
- **Black, CP442B - 32668**

**CP443W** 25353**Ajax VHF Bridge White**

- Number of potential outputs: 8
- Output types: Positive trip and negative trip (depends on the settings)
- Transmission types: Pulse and bistable (depends on the settings)
- Compatible with Ajax central units: Operates with Hub 2, Hub Plus, Hub 2 Plus
- VHF transmitter power: 12 V DC, 2 A
- Connection with a hub at a distance of up to 1800 meters
- The maximum battery size installed in the casing: 150 × 64 × 94 mm
- Backup battery is not included
- **Black, CP443B - 25352**

Warning Devices

**SW430** 7296**Ajax ocBridge Plus**

- Installation: Indoors
- Maximum number of detectors: 100
- Number of wireless inputs/outputs: 13
- Up to 2000m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Loops: NO/NC, EOL, 2EOL
- Power supply: 8 - 14 VDC
- MiniUSB - 5 V (only for setup)
- Dimensions: 95 × 92 × 18 mm

**SW431** 5260**Ajax uartBridge**

- Installation: Indoors
- Maximum number of detectors: 85
- Operating frequencies - 868.0 - 868.6 MHz
- Power supply voltage: 5 VDC
- Up to 2000m in an open space (in a perfect environment)
- Interface: UART
- Dimensions: 64 × 55 × 13 mm

**SD420W** 8697**Ajax HomeSiren White**

- Sound volume level: Adjustable, 81 - 105 dB at a distance of 1 m
- Alarm length: Adjustable, 3 - 180 sec
- Battery: 2 x CR123A batteries, 3 V
- Battery life: up to 5 years
- Up to 2000m in an open space (in a perfect environment)
- Protection class: IP50
- Certification: Grade 2, CE
- Dimensions: 75 × 76 × 27 mm
- **Black, SD420B - 8681**



Also available in black

SD421W 7830**Ajax StreetSiren White**

- Sound volume level: Adjustable, 85 - 113 dB at a distance of 1 m
- Power supply: 4 × CR123A, 3 V
- External supply: 12 VDC, 1.5 A
- Battery life: up to 5 years
- Up to 1500m in an open space (in a perfect environment)
- Protection class: IP54
- Dimensions: 200 × 200 × 51 mm
- **Black, SD421B - 7661**

Sensors

**FR422W** 43376.136.WH1**Ajax FireProtect 2**

- Interconnected alarm in 20 seconds
- Heat and Smoke Sensors
- Replaceable battery
- Remote control and configuration
- Smart Bracket with an adjustable rotation angle
- Dust proof smoke chamber and impenetrable for insects
- Dual-spectrum optical smoke sensor with false alarm filter

**FR423W** 43378.137.WH1**Ajax FireProtect 2**

- Interconnected alarm in 20 seconds
- Heat and Smoke Sensors
- Replaceable battery
- Dual-spectrum optical smoke sensor with false alarm filter
- Smart Bracket with an adjustable rotation angle
- Dust proof smoke chamber and impenetrable for insects

**FR424B****Ajax Manual Call Point Blue**

- Up to 7 years of battery life
- LED indication of the alarm state
- Transparent front lid to prevent accidental alarm activation
- Tamper Alarm
- Automation scenarios activation
- Alarm delivery to CMS

**FR424R****Ajax Manual Call Point Red**

- Up to 7 years of battery life
- LED indication of the alarm state
- Transparent front lid to prevent accidental alarm activation
- Tamper Alarm
- Automation scenarios activation
- Alarm delivery to CMS

Accessories



SW429W 8050

Ajax LeaksProtect White

- Installation: Indoors
- Up to 1300m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Power supply: 2 x AAA batteries, 3 V
- Battery life: up to 5 years
- Protection class: IP65
- Dimensions: 56 × 56 × 14 mm



SW423B 7649

Ajax Wall Switch Black

- Installation method: into wall plate
- Maximum load current: 13A
- Relay: NO/NC
- Operates with all Ajax Hub and range extenders
- Up to 1000m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Power supply: 110 - 230 VAC
- Dimensions: 39 × 33 × 18 mm



SW426 11035

Ajax Relay

- Power supply: 7 - 24 VDC
- Maximum load current: 5A at 36 VDC, 13A at 230 VAC
- Relay: NO/NC
- Operating frequencies - 868.0 - 868.6 MHz
- Dimensions: 39 × 33 × 18 mm



SW427 10306

Ajax Transmitter

- Power supply output: 3.3 VDC
- Battery life: up to 5 years
- Up to 1700m in an open space (in a perfect environment)
- Operating frequencies - 868.0 - 868.6 MHz
- Dimensions: 100 × 39 × 22 mm



SW428W 13305

Ajax Socket White

- Maximum load current: 11 A (continuous) or 13 A (up to 5 sec)
- Up to 1000m in an open space (in a perfect environment)
- Executes scenarios
- Relay: NO/NC
- Pulse duration: 0.5 - 255 sec
- Operating frequencies - 868.0 - 868.6 MHz
- Operating voltage: 110 - 230 VAC
- Output power: up to 2.5 kW
- Dimensions: 65.5 × 45 × 45 mm



SW434W 42982

Ajax LifeQuality White

- Monitors Carbon dioxide/ Temperature/Humidity
- Built-in accelerometer
- Can be installed on Ceiling/Wall or on table
- Remote control and configuration
- Non-dispersive infrared sensor for precise CO2 measurement
- Up to 3 years battery life
- **Black, SW434B - 42983**



SW433W 50535

Ajax WaterStop 3/4 (3 quarter)


- 4 mounting positions
- Compatible with cold and hot water pipes
- Water shut-off in 5 seconds
- Automatic Stuck prevention
- Optional Power supply
- In-App notifications
- Remote control and configuration
- **Black 1/2 (HALF), SW433B - 45644**



SW423-1 40696

Ajax DIN Holder Bracket


- Weight: 9g
- Operating temperature: -25°C to +60°C
- Material: Polycarbonate
- Color: Black only
- Dimensions: 52 × 41 × 18 mm




AUTOMATION

Smart sockets & relays allow you to control and automate electric locks, gates, boilers and other appliances using the

Ajax App.



Complete Wireless Security Solutions From Ajax



- BD427W - MotionProtect OutDoor
- CC550W - MotionCam
- SW420W - Button
- SW423B - WallSwitch
- SD421W - StreetSiren
- CP424W - Hub 2 4G
- CP430W - Keypad
- SW429W - LeakProtect
- BD420W - MotionProtect
- FR424W - FireProtect

*Selected products available in black

CONTACT US

BRANCHES

Gauteng

Alberton: 087 537 4166
 Balfour Park: 011 640 2288
 Boksburg: 011 918 8505
 Centurion: 012 653 0653
 Edenvale: 011 453 0229
 Fourways: 011 467 8817
 Krugersdorp: 087 092 8100
 Linden: 011 888 5666
 Longmeadow: 011 454 8009
 Lynnwood: 012 460 4550
 Midrand: 011 312 7576
 Montana: 087 802 3939
 Roodepoort: 011 760 1149
 Strijdom Park: 011 791 4770
 Vanderbijlpark: 016 931 0116
 Xavier (JHB South): 011 433 8943
 Exports: 087 537 4100

Eastern Cape

East London: 043 735 4537
 Gqeberha (PE): 041 364 3885

Free State

Bloemfontein: 051 447 6969

KwaZulu Natal

Durban: 031 263 0901
 Pietermaritzburg: 087 803 4544
 Pinetown: 031 701 3222

Mpumalanga

Emalahleni (Witbank): 013 656 4140
 Mbombela (Nelspruit): 013 753 2831

Limpopo

Polokwane: 015 296 0531

Western Cape

Bellville: 021 949 6330
 George: 087 537 4155
 Northgate: 021 510 1411
 Ottery: 021 745 4989

CUSTOMER SUPPORT

Accounts

email
accounts@regalsecurity.co.za

Sales

email
sales@regalsecurity.co.za

National Support Centre

Tel: 087 802 3920
 email
nsc.support@regalsecurity.co.za

Need Technical Support?

Call ANY Regal branch and dial 2

SCAN TO VIEW ALL
REGAL BROCHURES



WhatsApp us on **081 475 5079**

